



S N O W P L O W

FORGE SPREADERS

APPLICATIONS: 1/2 TON TRUCKS & 3/4 TO 1-TON TRUCKS



For questions or to place an order, contact HAWKEYE TRUCK EQUIPMENT at 515-289-1755 or 1-800-622-8223.

SPECIFICATIONS	FORGE 2.0 Auger Spreader	FORGE 2.0 Pintle Chain Spreader
Hopper Capacity	2 Yards - 2 cubic yards (1.53 cubic meters)	2 Yards - 2 cubic yards (1.53 cubic meters)
Hopper Length	70" (178 cm)	70" (178 cm)
Hopper Height	38" (96.5 cm)	38" (96.5 cm)
Hopper Width	48" (122 cm)	48" (122 cm)
Spreader Overall Length	98" (249 cm)	98" (249 cm)
Spreader Weight (Empty)	650 lb (295 kg)	700 lb (318 kg)
Hopper Construction	14ga Stainless Steel	14ga Stainless Steel
Spreading Width	2 ft-40 ft (0.6 m - 12 m)	2 ft-40 ft (0.6 m - 12 m)
Max Feed Rate	2.3 cu ft (0.06 cu m) per minute	4.0 cu ft (0.11 cu m) per minute
Work Lighting	Optional	Optional
Cover	Optional	Optional
Top Screen	Standard	Standard
Gearbox and Ratio	Planetary 91:1	Planetary 91:1
Motor	1/2 HP Motor	1/2 HP Motor
Trough	11ga Stainless Steel	11ga Stainless Steel
Control	Dual Variable Speed	Dual Variable Speed
Vibrators	1 Standard	Optional
Inverted V Baffle	Standard	Optional
Material Conveying Method	6" (15 cm) OD X 9" (23 cm) Pitch Full Length Auger	14" (36 cm) Wide Pintle Chain
LED CHMSL	Standard	Standard
Adjustable Deflector	Standard	Standard
Spinner Assembly	Easily Removable/Swing Out	Easily Removable/Swing Out
Hopper Tie-Down Kit	Standard	Standard
Spinner	14.5" (36.8 cm) Diameter Urethane Spinner	14.5" (36.8 cm) Diameter Urethane Spinner
Spinner Gearmotor	1/8 HP Gearmotor (Located Above Spinner)	1/8 HP Gearmotor (Located Above Spinner)
Minimum Bed Length	6' 6" (168 cm)	6' 6" (168 cm)
Minimum GVWR	10,000 lb (4,535 kg)	10,000 lb (4,535 kg)

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

©2017 BOSS Products/The Toro Company. All rights reserved. Patents: www.ttcopats.com