

# AMERICAN EAGLE®

## COMPRESSOR AND ACCESSORIES CATALOG



What work trucks  
are built around.

For questions or to  
place an order, contact  
**HAWKEYE TRUCK EQUIPMENT**  
at 515-289-1755 or 1-800-622-8223



Specifications may change without notification.

American Eagle and the American Eagle logo are registered with the  
U.S. Patent and Trademark Office.

Copyright © 2015 American Eagle Accessories Group

# Two-Stage Piston Series

## AMERICAN EAGLE®

## COMPRESSORS

**All two-stage hydraulic-driven units include a heavy-duty commercial grade two-stage reciprocating pump for reliable performance.**

- Cast-iron, one piece cylinder and head design - no head gaskets to fail!
- Domed head design for high efficiency.
- Cast iron crankcase for durability.
- Reliable, high flow disc valves for trouble-free performance and long life.
- Heavy-duty fully balanced pistons, crankshaft, and fan bladed flywheel for smooth, cool operation.
- Heavy-duty crankshaft main roller bearings for long life.
- Oil level sight glass for easy visual check.
- Intercoolers for cooling between stages for increased efficiency and life.
- High-capacity hydraulic oil cooler and fan for cooler operation.
- Canister type air filters for high capacity and easy changing.
- Model 46P includes a durable and attractive white painted steel cover. The cover features a hinged lid for quick access to all maintenance points. (Cover is optional on model 23P).
- Options include hydraulic oil reservoir and/or air tank.
- Five-year limited warranty on compressor (pump) for peace of mind.



### Model 23P

- 23 cfm @ 175 psi
  - Hyd. req: 8 gpm @ 2300 psi
  - Max. pressure: 175 psi
  - Two-stage, Two-cylinder
  - 28"L x 19.5"W x 27.5"H
  - Weight: 325 lbs
- (Shown with optional 8 gal. hyd reservoir)



### Model 46P

- 46 cfm @ 175 psi
- Hyd. req: 17-19 gpm @ 2500 psi
- Max. pressure: 175 psi
- Two-stage, Four-cylinder
- 33.5"L x 25"W x 27.5"H
- Weight: 425 lbs



### Model 60P

- 60 cfm @ 175 psi
- Hyd. req: 16 gpm @ 2300 psi
- Max. pressure: 175 psi
- Two-stage, Two-cylinder
- 46"L x 24"W x 35"H
- Weight: 655 lbs



### Model 110P

- 110 cfm @ 175 psi
- Hyd. req: 24 gpm @ 2300 psi
- Max. pressure: 175 psi
- Two-stage, Four-cylinder
- 43"L x 28"W x 36.5"H
- Weight: 900 lbs