

DVS (Dump V-Box Spreader)

DVS



Standard Specifications:

- $\frac{3}{16}$ " Mild Steel Body
- $\frac{3}{16}$ " Formed Dirt Shedding Top Rail
- $\frac{3}{16}$ " Removable Chain Shields (For Ease of Maintenance)
- $\frac{1}{4}$ " Long sills 14" in Height with Formed Cross sills
- $\frac{1}{4}$ " Replaceable Floor, Supported on 12" centers
- 2" Drive and Idler Shafts with 2" Heavy Duty Bearings
- $1\frac{1}{4}$ " Heavy Duty Chain Adjusters
- Case Hardened Sprockets to 40-48 Rockwell
- 34" Wide Conveyor with $\frac{1}{2}$ " x $1\frac{1}{2}$ " Bar Flights on $4\frac{1}{2}$ " Centers
- Heavy Duty Pintle Chain with a 26,000 Minimum Tensile Strength Rating
- Telescopic Double Acting Nitrated Hoist Cylinder
- Full Opening Double Acting Tailgate
- Receiver Tube Mounted Rear Spinner Assembly



Options:

- Corrosion-Resistant Stainless Steel Construction
- High Temp Belt-Over-Chain Main Conveyor
- Bar Every Link, 2.25" Pitch
- Ladder in Mild or Stainless Steel
- Side Boards of Mild or Stainless Steel
- Optional Spinner Chutes
- Variety of Light Packages
- Variety of Cab Protectors
- Asphalt chute or Patch Pan
- Top Screens
- Grease Line Extension



For questions or to place an order, contact HAWKEYE TRUCK EQUIPMENT at 515-289-1755 or 1-800-622-8223.