



TRAILERS & TRUCK BODIES



WABF1966-2 ALUMINUM MONOSHELL END DUMP BODY SHOWN

*Rage*<sup>TM</sup>

**Aluminum End Dump Body  
Single Wall Monoshell**



# Rage™

## Specifications

LENGTH	10'-0" – 24'-0" Aluminum MONOSHELL
OUTSIDE WIDTH	96"
SIDE HEIGHT	42" to 72"
BULKHEAD	48" to 72"
CAPACITY	10 – 30 cubic yards
SIDE MATERIAL GA.	3/16" or 1/4"
BULKHEAD MATERIAL GA.	3/16" or 1/4"
VERTICAL SIDE BRACES	Front & Rear - (Intermediate optional)
TOP SIDE RAILS	4", 6" or 9" boxed top w/ (2) or (3) stripes;
BOTTOM SIDE	Integral smooth 6061-T6
SIDEBOARDS / CAP ANGLE	Wood, Flush or Inverted angle
TARP BAR	NONE
STEPS & LADDERS	Driver side front in & out & rear panel out only
LIGHTS	FMVSS-108 (3)Markers each side bottom only; Mdl. 60 oval rear posts;
FLOOR MATERIAL GA	1/4"
CROSSMEMBERS	None STD - 3" x 3" boxed 18" on center spacing optional
TAILGATE	3/16" thick plate; Spring/Air chamber lock with frame control and gladhand to front; 3", 6", 12" or 24" slope;
LIGHTGUARD APRON	OPTIONAL
SPLASH GUARDS FRONT	14"x24" alum w/ 12"x24" front of tire;
MUD FLAPS REAR	12"x24" rubber on front corner fenders
FINISH / BODY	(2)24"x42" rubber mtd on angled brackets
HOIST	(1)full rubber center frame (all across rear)
SILLS	Bright natural aluminum
BODY HINGE	Hyva, Custom & Mailhot front telescopic, pin to pin STD or trunnion
HYD PUMP	Rubber in integral body track
PTO	1-3/4" diameter angle frame
HYD TANK	Direct mount 35 gpm, 2.5" gear width
BACK-UP ALARM	Direct mount
LIFT AXLE	Side or upright mount aluminum
PINTLE HOOK	level / temp gauge and shut-off valve
INSTALLATION	102db electric
OPTIONAL	Optional
	Optional
	Factory or ship-out
	Rear body lights, reverse taper backend, added lighting, tailgate material door(s), floor center crossmembers, material thickness, poly floor liners, tarps



**Rhodes Trailers & Truck Bodies**

28 S First Street • Parkersburg, WV 26101 • Phone (800) 419-5821 • Fax (304) 863-8772

[www.rhodestrailers.com](http://www.rhodestrailers.com)