

AMERICAN EAGLE®

COMPRESSOR AND ACCESSORIES CATALOG



What work trucks
are built around.

For questions or to
place an order, contact
HAWKEYE TRUCK EQUIPMENT
at 515-289-1755 or 1-800-622-8223



Specifications may change without notification.

American Eagle and the American Eagle logo are registered with the
U.S. Patent and Trademark Office.

Copyright © 2015 American Eagle Accessories Group

Single-Stage Piston Series

AMERICAN EAGLE®

COMPRESSORS

The single-stage compressors are manufactured for reliability and longevity.

- Direct-drive, no belts to break or adjust.
- Cast iron crankcase and cylinder heads for durability.
- High temperature precision ground 4-ring pistons for consistent performance.
- Stainless steel reed valves for long life and heat resistance.
- Heavy ductile iron balanced crankshaft with heavy-duty journal bushings and micro-honed connecting rods for smooth operation and long life.
- High-capacity hydraulic oil cooler and fan for cooler operation.
- Canister type air filters for high capacity and easy changing.

- Models 8P and 13P include fiberglass covers that flip-up for quick access to all maintenance points.
- Models 30P and 70P include durable and attractive white painted steel covers. These covers feature hinged lids for quick access to all maintenance points.
- All single-stage hydraulic-driven units include a single-stage reciprocating pump.

Options include:

- Hydraulic oil reservoir under compressor.



Model 8P

- 8 cfm @ 100 psi
- Hyd. req: 7 gpm @ 1800 psi
- Max. pressure: 150 psi
- Single-stage, Two-cylinder
- Imbedded air filter
- 23"L x 14.5"W x 17"H
- Weight: 125 lbs
- Uses Model 143 Pump



Model 30P

- 30 cfm @ 100 psi
- Hyd. req: 11 gpm @ 1850 psi
- Max. pressure: 150 psi
- Single-stage, Four-cylinder
- Canister air filter
- 26"L x 18"W x 17.5"H
- Weight: 235 lbs
- Uses Model V480 Pump



Model 13P

- 13 cfm @ 100 psi
- Hyd. req: 7 gpm @ 1800 psi
- Max. pressure: 150 psi
- Single-stage, Two-cylinder
- Imbedded air filter
- 26"L x 14.5"W x 17"H
- Weight: 125 lbs
- Uses Model 200 Pump



Model 70P

- 70 cfm @ 100 psi
- Hyd. req: 18 gpm @ 2650 psi
- Max. pressure: 150 psi
- Single-stage, Four-cylinder
- Canister air filter
- 31"L x 22.5"W x 22"H
- Weight: 300 lbs
- Uses Model HV60 Pump