

DUMP INSERTS



STEEL & STAINLESS STEEL 6FT. & 8FT. MODELS POLYMER 8FT. MODEL



FEATURES & OPTIONS

PART NUMBERS

- 5531000 8' Steel Insert
- 5531006 6' Steel Insert
- 5534000 8' Stainless Steel Insert
- 5534006 6' Stainless Steel Insert

STANDARD FEATURES

- Fits Most 8' and 6' Beds
- Power Up and Power Down
- 1.5Kw motor (3 HP max) for Hydraulic Pump
- 2 cu yd capacity (8'); 1.5 cu yd capacity(6')
- Payload capacity: 6,000 lbs. max*
- Dump Angle 0°– 45°
- 12 Gauge Steel Black Powder Coat Finish or 304 Stainless Steel (front, sides, floor)
- Includes Manual Safety Bar
- Tethered Control Box with 6' Cord
- Grease Fittings/Holes in Pivot Points
- Includes Body-Up Indicator Kit (SK10)
- 20' Battery Cables
- Tailgate Chains
- Black Powder Coat Structural Steel Frame
- Double Pivoting and Removable Steel or Stainless Steel Tailgate
- 3/4" Diameter Tailgate Hinge Pins

OPTIONS

- 5531010 Bolt-On Cab Guard for 6' & 8' Steel Insert
- 5531020 ** Wall Extension Bracket Kit for 6' & 8' Steel Insert (hardware & 2 brackets per side), accepts one 2" x 12" per side
- 5534010 Stainless Steel Bolt-On Cab Guard for 6' & 8' Stainless Steel Insert
- 5534020 **- Stainless Steel Wall Extension Bracket Kit for 6' & 8' Stainless Steel Insert (includes hardware & 2 brackets per side), accepts one 2" x 12" per side
- DTR5508 ***- Roll Tarp Kit, 5.4'W x 9.5'L for 6' Steel/ Stainless Steel Inserts
- DTR5511 ***- Roll Tarp Kit, 5.4'W x 11.5'L for 8' Steel/ Stainless Steel Inserts

* weight limits not to exceed manufacturers gross vehicle weight limits ** for use with Steel/Stainless Steel DumperDogg® inserts with cab guard installed (2" x 12" not included) *** must be used with cab guard

DumperDogg



0° - 45° Dump Angle (Steel/SS & Poly Models)



Tethered Control Box (Steel/SS & Poly Models)



Structural Steel Frame (Steel/SS & Poly Models)



Optional Tarp Kits (Steel/SS & Poly Models)



Body-Up Indicator Kit (Steel/SS & Poly Models)



Grease Fittings/Holes (Steel/SS & Poly Models)



3/4" Dia. Tailgate Hinge Pins (Steel/SS & Poly Models)



Optional Bolt-On Cab Guard (Steel/SS Models Only)

DumperDog

FEATURES & OPTIONS

PART NUMBERS

 5532000 - 8' Poly Insert STANDARD FEATURES

Fits Most 8' Beds
Power Up and Power Down
1.5Kw motor (3 HP max) for Hydraulic Pump

1.6 cu yd capacity
Payload capacity: 6,000 lbs. max*
Dump Angle 0°- 45°
Double Wall Poly Construction
Integral Steel Window Protector
Includes Manual Safety Bar
Tethered Control Box with 6' Cord
Grease Fittings/ Holes in Pivot Points
Includes Body-Up Indicator Kit (SK10)
Tailgate Chains
20' Battery Cables

Black Powder Coat Structural Steel Frame
 Double Pivoting and Removable Steel Tailgate
 3/4" Diameter Tailgate Hinge Pins

5531050 - Poly Wall Extensions for 8' Poly Insert
DTR4510 - Roll Tarp Kit, 4.6' x 10' for 8' Poly Insert

* weight limits not to exceed manufacturers gross vehicle weight limits



Motor & Hydraulic Pump (Steel/SS & Poly Models)



Double Pivoting Tailgate (Steel/SS & Poly Models)



Circuit Breaker (Steel/SS & Poly Models)



Optional Poly Wall Extensions (Poly Model Only)

DumperDo



Manual Safety Bar (Steel/SS & Poly Models)



Double Pivoting Tailgate (Steel/SS & Poly Models)



Steel Window Protector (Poly Model Only)



Optional Wall Extension Bracket Kit (Steel/SS Models Only)



TAINLESS STEEL

FEATURES

1. 1.

- Part No.: 5535000
- All stainless steel construction won't rust or corrode
- 12VDC Spinner Motor 54 AMP/ 620 RPM
- 12VDC Auger Gear Motor 50 AMP/ 30 RPM/ 1042 in Ibs.
- Adjustable spread pattern from 4' to 20' of rock salt, free-flowing granular materials or chemicals
- Includes in-cab, independent variable spinner speed control and auger control
- Includes dual-flight augers (5" O.D. x 2.4" I.D. x 20"L) with mixing tines
- 14" Poly spinner

CLASSIN

- Overall Dimensions 64.5" W x 31" H x 16.5" D
- Weight: 280 lbs.
- Quick and Easy installation.

Fits all DumperDogg[®] Dump Inserts



For questions or to place an order, please contact HAWKEYE TRUCK EQUIPMENT at 515-289-1755 or 1-800-622-8223.