## **MUNICIPAL HOPPER SPREADERS**

**BULK SALT** 

**CONVEYOR** 

**SAND/SALT MIX** 

For questions or to place an order, contact HAWKEYE TRUCK EQUIPMENT at 515-289-1755 or 1-800-622-8223.

## 10 - 16 Cu. Yards

Minimum 35,000 lbs., 38,000 lbs., 44,000 lbs, or 48,000 lbs. GVW chassis.

(see www.SaltDogg.com for specs by model number)

- Capacity: 10 to 16 cu. yds. (12' to 15').
- 304 stainless steel hopper
- Material spread up to 40'.
- Power Source: Hydraulic Drive two independent direct drive hydraulic motors (17 GPM @ 1,500 PSI). 15 gpm conveyor. 12 gpm spinner.
- Chute/Spinner Assembly: 304 stainless steel, with adjustments to accommodate varying body mounting heights. 6-fin poly spinner disc. Adjustable deflectors with overlapping corners provide a precision spread pattern.
- Feedgate: 304 stainless steel with scaled driver side screw jack adjustment.
- Conveyor: 24" wide with 2" diameter drive shaft. 50:1, 25:1 or 6:1 direct-drive gearbox with extended throughshaft for ground speed sensor. 1-1/2" diameter idler shaft with 4" adjustable range relubeable bearing.
- Includes: 4-section hinged top screens, stainless steel inverted V

