

One Way High Speed Slotted Trip



Moldboard Thickness:	10 Gauge
No. of 1/2" Vertical Ribs:	7
Moldboard Reinforcing:	1 piece, 1/2" Flame Cut Ribs
Moldboard Top Angle:	2" x 3" x 3/8"
Adjustable Moldboard Pitch Settings:	20° to 50°
Bottom Moldboard Angle:	4" x 6" x 1/2"
Reversing Limits (left & right):	37°
Plow to Table Hinge Points:	4
Cutting Edge:	5/8" x 8" Top Punched
Pivot Pin:	1/4" Stopped

Q) I plow long runs of open rural highways. Should I choose Monroe's high speed slotted trip one way?

A) This is a higher speed rural plow that will pick up the snow fast and discharge it fast. Designed for deep snow and high speed operation; minimum 15MPH. Higher speeds permit the snow to be cast away much further with this plow. The slotted trip assemblies protect the plow by allowing the cutting edge and moldboard to slide up in slots to clear an object, compressing the springs, then returning to the plowing position after clearing the obstruction. The pushframe has to be supported to make this work so skid shoes are standard. This is a very heavy, good cleaning snowplow.

Plow Model No.	Overall Length	Moldboard Height Nose	Cutting Edge Height Discharge	Approx. Weight (lbs)
MPHS26-54-11-ISST	13'10"	26"	54"	2250
MPHS35-64-11-ISST	14'4"	35"	64"	2410
MPHS45-72-11-ISST	14'4"	45"	72"	2450
MPHS26-56-12-ISST	14'9"	26"	56"	2310
MPHS35-66-12-ISST	15'10"	35"	66"	2470
MPHS45-72-12-ISST	15'10"	45"	72"	2525
MPHS25-67-11-OWIS	13'6"	25"	67"	2155
MPHS23-69-12-OWIS	14'7"	23"	69"	2263
MPHS36-62-11-OWIS	14'3"	36"	62"	2537
MPHS36-63-12-OWIS	15'4"	36"	63"	2625

For questions or to place an order, please contact **HAWKEYE TRUCK EQUIPMENT** at 515-289-1755 or 1-800-622-8223.

