

For questions or to place an order, contact
HAWKEYE TRUCK EQUIPMENT at
 515-289-1755 or 1-800-622-8223.

Rear Cross Conveyor

MS10312/MS10318

MS10312

GENERAL SPECIFICATIONS

WIDTH: 103"
 DEPTH*: 28.46 OAL
 HEIGHT*: 26.94 OAL
 ENDPLATES: 1/4"

CONVEYOR SPECIFICATIONS

ADJUSTABLE FEED GATE (X2): 10" X 10"
 DISCHARGE: LEFT AND/OR RIGHT
 BELT WIDTH: 12"
 BELT THICKNESS: 3/8"

MS10318

GENERAL SPECIFICATIONS

WIDTH: 103"
 DEPTH*: 34.46 OAL
 HEIGHT*: 26.94 OAL
 ENDPLATES: 1/4"

CONVEYOR SPECIFICATIONS

ADJUSTABLE FEED GATE (X2): 10" X 16"
 DISCHARGE: LEFT AND/OR RIGHT
 BELT WIDTH: 18"
 BELT THICKNESS: 3/8"



Shown with Optional Spinner Assembly and Berm Chute



Optional 4' Extension with caged rollers.

Features:

- Spreads A Wide Variety of Material Which Includes All Types of Aggregate and Hot Mix Asphalt.
- Performs Shoulder Maintenance, Rut-Filling, Asphalt-Patching and Ice Control.
- Available in a 12" or 18" Conveyor Width.
- Bi-directional Conveyor Provides Driver Side or Passenger Side Discharge.
- Quick Attach/Detach, Self-Leveling Mounting Hardware.
- Hi-Temp Straight Belt With Flexible Stainless Splicing.
- Caged Design Drive and Idler Pulleys.
- Poly Support Rollers with Stainless Steel Shaft, Which Eliminates the Need for Bearings.
- Heavy Duty Bearing and Belt Adjustment.

Options:

- 4' Extension with Belt to Mount to Hydraulic Truck Conveyor
- Light Package - Stop, Turn & Tail with 3-Light Cluster
- Sand Bag Attachment
- Corrosion-Resistant Stainless Steel
- Spinner Assembly
- Reversing Valve
- Berm Chute

Q: Why should I use a Monroe Rear Cross Conveyor Spreader?

A: The Monroe Rear Cross Conveyor spreader is designed to spread all types of aggregate, hot mix and even soil when used in conjunction with a standard dump body. It is ideal for shoulder maintenance, edge rut filling, patching and ice control. Available from Monroe in either a 12" or 18" wide belt, these versatile units are low-maintenance, self-cleaning units that are great for the small municipal entity that needs to spread abrasives in the winter, yet can't afford a separate shouldering machine for spring and summer work.



- Available in Manual or Hydraulic Actuation
- Bolt-On Replaceable 1/2" x 4" Skid Shoe Weldments
- 24" Wide Leveling Box
- Height Adjustable Leveling Blade
- Universal Left or Right Hand Mounts
- Can Be Raised Up and Out of the Way for Transport
- Unit Slides on Six Heavy Duty UHMW Slider Blocks for Better Support
- Powder Coat Black
- Available for Monroe MS10318 Rear Cross Conveyor
- 1/4" x 2-1/2" x 2-1/2" Slider Angles for Support of Leveling Box

Cross Conveyor
 Berm Master

